



ALARM CONTROL UNIT FOR FLAMMABLE GASES

3F+ input
Reversible IP65 enclosure

4 programmable relays

WARRANTY
3 YEAR



DALEMANS®
G A S D E T E C T I O N



U•H1

All gas detection installations must be calibrated and maintained regularly in accordance with the manufacturer's instructions to guarantee safety and performance.

CHARACTERISTICS

MANUFACTURER	Design and fabrication	DALEMANS SA
POWER SUPPLY	Mains	220-240 V (AC) ~ 50Hz
	Power	15 W max.
ENCLOSURE	Material	Plastic ABS-PC UL94 V-0
	Dimensions (excluding PE)	264 x 233 x 72 mm
	Weight without battery	1,2 kg
	Protection Degree	IP65
	Reversibility	Rotation of 180°
	Standard mounting	4 screws or mounting lugs
	Optional mounting	Mounting on DIN rail
CONNECTION	Cable inlets	2 x M20 and 4 x M16
	Screwed terminals	1 x 2,5 mm ² or 2 x 1,5 mm ² per terminal
INPUTS	Detector	1
	Type of detector	3F+ (analog 3-wire)
	Wiring length	up to 300 m
	Self-powered external alarm input 24V (DC)	1
OUTPUTS	Alarms: Addressable changeover relays max. 230V / 3A	3
	Fault: changeover relay max. 230V / 3A	1
	Transistor alarm	24 V (DC) - 200 mA max.
INTERFACE	Display	LCD backlighting of a variable colour
	Voltage indicator	Green LED
	Inhibition indicator	Yellow LED
	Technical fault indicator	Yellow LED
	Navigation and configuration	Using a membrane keypad
MAIN FUNCTIONS	Configurable alarm levels	2
	Access protection using password	YES
	Maintenance alert	YES
	Display of events and statuses	YES
	Customisable detector locations	YES
	Test and inhibition functions	YES
OPERATING CONDITIONS	Temperature	-10°C to +40°C
	Humidity & Pressure	10 à 90% RH (non-condensing) 90-110 kPa
	Altitude	2000 m max.
CERTIFICATIONS	Electromagnetic compatibility (EMC)	EN 50270 (type 1)
	Low-voltage safety	EN 61010-1
	Marking	CE, RoHS

The information contained in this document is non-contractual and subject to change

rue Jules Mélotte 27A | B-4350 Remicourt (Belgium)

+32 19 33 99 43 | sales@dalemans.com

www.dalemans.com